FILTER SOLUTION

Design, Supply & Support

One Stop Solution to your Filters Production

PLM-60L

Hot Melt Adhesive Melter



PLM brand concept

PLM brand appearance concept.
Final configuration subject to confirmation.

Scan for product details

HOT MELT ADHESIVE SYSTEMS

Features

- **Capacity reference:** 60 L tank capacity reference for storage and replenishment planning.
- **Pump options:** Single- or dual-pump options to match the required delivery conditions.
- **Hose connection options:** 4- or 6-hose connection options for matched application heads.
- **Electrical & installation:** AC 380 V, 50/60 Hz reference supply. Confirm melting capacity and installation needs for the selected build.

Applications

Review selected packaging, furniture, textile or foam lamination, filter manufacturing and general assembly processes. Confirm viscosity, dispensing or coating method, average and peak adhesive consumption and line interfaces. Storage volume alone does not guarantee speed or continuous output; reactive PUR requires a separately assessed setup.

Specification

- **Product Name:** PLM-60L
- **Tank capacity reference:** 60 L
- **Power Supply (reference):** AC 380 V 50/60 Hz
- **Hose connection options:** 4 or 6
- **Metering pump options:** Single or dual pump

Product details

View PLM-60L product information

Reference data. Final configuration and included items are defined in the technical offer.

ADD: East of Anping, hengshui city, Hebei province China
TEL: +86-15131850885 Whatsapp: +86-15131850885
WEB: www.pmfiltersolution.com
E-MAIL: info@pmfiltersolution.com